















Title		
Xplorer_GS32F0025_Connectors		
Size	Number	Revision
B	1	
Date:	8/06/2025	Sheet of
File:	D:\Desktop\Xplorer_GS32F0025_Connectors	Drawn by:




格见半导体 Draft Only

Gejian Semi. confidential - NDA Restrictions



格见半导体 Draft Only

Title			Xplorer_GS32F0025_Peripheral		
Size	Number	Revision			
B	2				
Date:	8/06/2025	Sheet of			
File:	D:\Desktop\Xplorer_GS32F0025_Peripheral	Drawn By:			





格见半导体 Draft Only

Gejian Semi. confidential - NDA Restrictions

Title			
Xplorer-GS32F0025_Power			
Size	Number	Revision	
B	5		
Date:	8/06/2025	Sheet of	
File:	D:\Desktop\Xplorer-GS32F0025_Power.Sch	Drawn By:	

GS32F002x Device




默认使用 GPIO41(EQEP) 和 GPIO22，电阻焊接

格见半导体 Draft Only


Gejian Semi. confidential - NDA Restrictions

Title			Xplorer-GS32F0025_Device	
Size	Number	Revision		
A3	3			
Date:	8/06/2025	Sheet of		
File:	D:\Desktop\...\Xplorer-GS32F0025_Device	Schematic By:		


USB




ESD




SPI



Oscillator





USB2UART



与板载调试器使用同一组串口，U10与U8 BOM 选择

Isolation Boundary



格见半导体 Draft Only

Gejian Semi. confidential - NDA Restrictions

Title			Xplorer-GS32F0025_FT2232		
Size	Number	Revision			
			4		
Date:	8/06/2025	Sheet of			
File:	D:\Desktop\...\Xplorer-GS32F0025_FT2232_Schematic.B	Drawn By:			

